

TBS-304

Infrared Beam Detector, 4 Beam



General Features

- 30m detection range
- Alarm triggered by simultaneous interruption of two adjacent beams
- NO/NC relay output 26V AC/DC, 0.5A maximum
- Tamper switch
- 11~18V DC, alarm current 100mA max.
- Length: 76cm; Width: 4cm.

TBS-306

Infrared Beam Detector, 6 Beam



General Features

- 30m detection range
- Alarm triggered by simultaneous interruption of two adjacent beams
- NO/NC relay output 26V AC/DC, 0.5A maximum
- Tamper switch
- 11~18V DC, alarm current 100mA max.
- Length: 108cm; Width: 4cm.

TBS-610

Infrared Beam Detector, 10 Beam



General Features

- 60m detection range
- Alarm triggered by simultaneous interruption of two adjacent beams
- NO/NC relay output 26V AC/DC, 0.5A maximum
- Tamper switch
- 11~18V DC, alarm current 100mA max.
- Length: 172cm; Width: 4cm.

TBS-612

Infrared Beam Detector, 12 Beam



General Features

- 60m detection range
- Alarm triggered by simultaneous interruption of two adjacent beams
- NO/NC relay output 26V AC/DC, 0.5A maximum
- Tamper switch
- 11~18V DC, alarm current 100mA max.
- Length: 204cm; Width: 4cm.