

TWS-1815

Wireless Sounder with Flasher

TWS-1815 works as sounder, flasher or both options at the same time according to project needs. It operates with 4pcs CR123A battery and communicates completely wirelessly with the control panel.

It has two different color options, white and red. Supports 3 different sound level along with 3 different flasher mode.



General Features


- EN54-3 and EN 54-25 Certified
- Approx. 500mt Wireless Coverage (Open Area)
- 6 Years Battery Lifetime with 4X CR123A Battery
- Only Sounder, Only Flasher or Both Options can be Operated
- 3 Different Sound Level
- 3 Different Flasher Mode (Slow, Normal, Fast)

Technical Specifications

EN 54-3

EN 54-25

	TWS-1815
Standard	EN54-3 and EN54-25
Operating Frequency	868 MHz
Radiated Power	Max. 14dBm (25 mW)
Number of Channel	10
Coverage	Approx. 1250 m. (Open Air)
Battery	Up to 8 Years With 4 x CR123A Battery
Sound Level	75 dB / 79 dB / 83 dB \pm 2 (@3 Vdc, 1m.)
Flasher Coverage	W-2,4-4
Sounder Mode	3 Modes (Low-Mid-High)
Sounder Tone Options	42 Different Tone
Flasher Mode	3 Modes (Slow-Normal-Fast)
Operating Temperature	-10°C ~ 55°C
Housing Material	RED / White - UL94 non-flammability Polycarbonate
Dimensions (mm)	Ø:110mm, h:48mm (without base)
Wight (incl. base / excl. base)	200gr. / 155gr. (batteries not included)
Humidity	95% RH
Protection Class	IP21C



Teknim Elektronik SAN. ve TİC. A.Ş

Dudullu Organize Sanayi Bölgesi 1.Cadde İsmet Tarman İş Merkezi No:1/32 Ümraniye-İSTANBUL

P: +90 (216) 455 88 46 - sales@teknim.com
www.teknim.com