

## TWB-1966

### Wireless Manual Call Point

The TWB-1966 is a wireless manual call point designed to manually trigger alarms in the event of a fire. It communicates entirely wirelessly with the wireless coordinator. With two batteries, the TWB-1966 can operate for up to 8 years. It features a resettable mechanism, and an optional protective cover can be added to prevent false alarms.

#### General Features

- TLPWAN Low Power, Two-Way Safe and Stable Wireless Communication Protocol
- EN54-11 and EN 54-25 Certified
- Bi-directional Wireless Communication
- Approx. 1250 m. Wireless Coverage (Open Air)
- Up to 8 Years Battery Lifetime with 2 x CR123A Battery
- Adaptive Power Management Algorithm for Ultra Low Power
- Resettable Type of Operation
- Status LED
- Low Battery and Tamper Warning
- Optional Protection Cover (TFA-0165)
- Flush or Surface Mounting Option



EN 54-11

EN 54-25

#### Technical Specifications

	TWB-1966
Standard	EN54-11 and EN54-25
Operating Frequency	868 MHz
Radiated Power	Max. 14dBm (25 mW)
Number of Channel	10
Coverage	Approx. 1250 m. (Open Air)
Battery	Up to 8 years
Operation Types	Resettable - A
Usage Area	Indoor Area
Operating Temperature	-10°C ~ 55°C
Dimensions (mm)	88.5x55.7x88.8 mm
Weight	155 gr
Humidity	95% RH(max.)
Protection Class	IP30

